



1 Identification of substance

· **Product details**

· **Trade name:** 38061-38194 Rust Shield RTS

· **Article number:**

38061, 38064, 38071, 38074, 38081, 38084, 38091, 38094, 38101, 38104, 38111, 38114, 38121, 38124, 38131, 38134, 38141, 38144, 38151, 38154, 38161, 38164, 38171, 38174, 38181, 39184, 39191, 39194

· **Manufacturer/Supplier:**

SEM Products Inc.
651 Michael Wylie Dr.
Charlotte, NC 28217
(704)522-1006

· **Information department:**

labsupport@sem.ws : SEM Products 651 Michael Wylie Dr. Charlotte, NC 28217 : phone 1-704-522-1006, M-TH 7am - 4pm EDT

· **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/Data on components

· **Chemical characterization**

· **Description:** Mixture of the substances listed below with nonhazardous additions.







· **Dangerous components:**

	ALKYD RESIN Warning: 3.2/2, 3.3/2A, 3.8/3	25-50%
14807-96-6	Talc (Mg3H2(SiO3)4) Warning: 3.2/2, 3.3/2A, 3.8/3	10-25%
1330-20-7	xylene Danger: 3.1.D/3, 3.1.I/4, 3.2/2 Warning: 2.6/3	10-25%
107-87-9	pentan-2-one Danger: 2.6/2 Warning: 3.2/2, 3.3/2A, 3.8/3	2.5-10%
14808-60-7	Quartz (SiO2) Danger: 3.6/1B, 3.8/2 Warning: 3.3/2A	2.5-10%
67-64-1	acetone Danger: 2.6/2 Warning: 3.3/2A, 3.8/3	2.5-10%
1333-86-4	Carbon black Warning: 3.2/2, 3.3/2A, 3.8/3	1-2.5%
	ACRYLIC RESIN Warning: 3.2/2, 3.3/2A, 3.8/3	1-2.5%
108-88-3	toluene Danger: 2.6/2; 3.10/1, 3.7/2 Warning: 3.2/2, 3.3/2A, 3.8/3	1-2.5%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene Warning: 2.6/3; 3.2/2, 3.3/2A, 3.8/3	1-2.5%

(Contd. on page 2)

Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 1)

123-86-4	<i>n</i> -butyl acetate Warning:  2.6/3;  3.8/3	1-2.5%
111-76-2	2-butoxyethanol Danger:  3.1.O/3, 3.1.D/3, 3.1.I/4, 3.2/2, 3.3/2A Warning: 2.6/4	1-2.5%
67-56-1	methanol Danger:  2.6/2;  3.1.O/2, 3.1.D/2, 3.1.I/2;  3.8/1	≤1%

3 Hazards identification

· **Hazard description:**



Toxic
Highly flammable

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

May cause cancer by inhalation.

Highly flammable.

Harmful by inhalation and in contact with skin.

Irritating to eyes, respiratory system and skin.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

· **GHS label elements**



Danger

2.6/2 - Highly flammable liquid and vapour.



Danger

3.6/1B - May cause cancer.

(Contd. on page 3)

Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 2)



3.1/4 - Harmful in contact with skin.

3.1/4 - Harmful if inhaled.

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

Specific measures (see label).

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 3)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)



Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 4)

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

107-87-9 pentan-2-one

PEL	700 mg/m ³ , 200 ppm
REL	530 mg/m ³ , 150 ppm
TLV	Short-term value: 529 mg/m ³ , 150 ppm

14808-60-7 Quartz (SiO₂)

PEL	see Quartz listing
REL	0.05* mg/m ³ *respirable dust
TLV	0.025 R mg/m ³

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm BEI

1333-86-4 Carbon black

PEL	3.5 mg/m ³
REL	3.5* mg/m ³ *0.1 in presence of PAHs, as PAHs; 10-hr TWA
TLV	3.5 mg/m ³

108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	75 mg/m ³ , 20 ppm

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

111-76-2 2-butoxyethanol

PEL	240 mg/m ³ , 50 ppm Skin
REL	24 mg/m ³ , 5 ppm Skin
TLV	97 mg/m ³ , 20 ppm

(Contd. on page 6)

Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 5)

67-56-1 methanol

PEL	260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm
	Skin; BEI

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic

(Contd. on page 7)



Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 6)

· Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 56°C (133°F)	
· Flash point:	-19°C (-2°F)
· Ignition temperature:	500°C (932°F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
· Vapor pressure at 20°C (68°F):	6.7 hPa (5 mm Hg)
· Density at 20°C (68°F):	1.18 g/cm ³
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	37.6 %
VOC content:	32.7 %
	395.0 g/l / 3.30 lb/gl
· Solids content:	61.4 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

(Contd. on page 8)

Trade name: 38061-38194 Rust Shield RTS

Carcinogenic if inhaled.

(Contd. of page 7)

12 Ecological information

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

· **Product:**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN1263
- **Packing group:** II
- **Proper shipping name (technical name):** PAINT
- **Label:** 3

· **Land transport TDG (Canada) and ADR/RID (Europe):**



- **Hazard class:** 3 Flammable liquids
- **UN-Number:** 1263
- **Packaging group:** II
- **Label:** 3
- **Description of goods:** 1263 PAINT, special provision 640D

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1263

(Contd. on page 9)

Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 8)

- **Label** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-D
- **Marine pollutant:** No
- **Propper shipping name:** PAINT

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label** 3
- **Packaging group:** II
- **Propper shipping name:** PAINT

· **UN "Model Regulation":** UN1263; PAINT; 3; II

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

14807-96-6	Talc (Mg3H2(SiO3)4)
1330-20-7	xylene
	ACRYLIC RESIN
108-88-3	toluene
78-93-3	butanone
108-10-1	4-methylpentan-2-one
67-63-0	propan-2-ol
67-56-1	methanol
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

14807-96-6	Talc (Mg3H2(SiO3)4)
1330-20-7	xylene
107-87-9	pentan-2-one
14808-60-7	Quartz (SiO2)
67-64-1	acetone
1333-86-4	Carbon black
108-88-3	toluene
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
123-86-4	n-butyl acetate
111-76-2	2-butoxyethanol

(Contd. on page 10)



Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 9)

78-93-3	butanone
108-10-1	4-methylpentan-2-one
67-63-0	propan-2-ol
67-56-1	methanol
100-41-4	ethylbenzene

· Proposition 65

· Chemicals known to cause cancer:

1330-20-7	xylene
14808-60-7	Quartz (SiO ₂)
1333-86-4	Carbon black
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

1330-20-7	xylene	D
67-64-1	acetone	D
108-88-3	toluene	D
78-93-3	butanone	D
100-41-4	ethylbenzene	D

· IARC (International Agency for Research on Cancer)

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
1330-20-7	xylene	3
14808-60-7	Quartz (SiO ₂)	1
1333-86-4	Carbon black	2B
108-88-3	toluene	3
111-76-2	2-butoxyethanol	3
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	TRACE AMOUNTS OF 14808-60-7
67-63-0	propan-2-ol	3
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· TLV (Threshold Limit Value established by ACGIH)

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1330-20-7	xylene	A4
14808-60-7	Quartz (SiO ₂)	A2
67-64-1	acetone	A4

(Contd. on page 11)



Trade name: 38061-38194 Rust Shield RTS

(Contd. of page 10)

1333-86-4	Carbon black	A4
108-88-3	toluene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
1333-86-4	Carbon black

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Toxic
Highly flammable

· **Hazard-determining components of labelling:**

xylene
Quartz (SiO₂)

· **Risk phrases:**

May cause cancer by inhalation.
Highly flammable.
Harmful by inhalation and in contact with skin.
Irritating to eyes, respiratory system and skin.

· **Safety phrases:**

Avoid exposure - obtain special instructions before use.
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
Wear suitable protective clothing, gloves and eye/face protection.
In case of insufficient ventilation, wear suitable respiratory equipment.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement internationale concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

Material Safety Data Sheet
acc. to ISO/DIS 11014



Printing date 01/24/2008

Reviewed on 01/24/2008

Trade name: 38061-38194 Rust Shield RTS

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

(Contd. of page 11)

USA