

## 1 Identification of substance

- **Product details**
- **Trade name:** 39463 Undercoating
- **Article number:** 39463
- **Manufacturer/Supplier:**  
SEM Products, Inc.  
651 Michael Wylie Dr.  
Charlotte, NC 28217  
USA  
(704)522-1006
- **Information department:** 24HR EMERGENCY CHEMTREC 800-424-9300

## 2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

8052-42-4	Asphalt	25-50%
68476-86-8	Petroleum gases, liquefied, sweetened	25-50%
64742-89-8	Solvent naphtha (petroleum), light aliph.	10-25%
8052-41-3	Stoddard solvent	2.5-10%
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	2.5-10%
108-88-3	toluene	2.5-10%
67-56-1	methanol	≤ 2.5%

## 3 Hazards identification

- **Hazard description:**



Harmful  
Extremely flammable

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

Extremely flammable.

Harmful if swallowed.

Irritating to eyes, respiratory system and skin.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

52.9 % by mass of the contents are flammable

Keep out of the reach of children.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

Trade name: 39463 Undercoating

(Contd. of page 1)

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



#### 4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Immediately call a doctor.

#### 5 Fire fighting measures

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** No special measures required.

#### 6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

#### 7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

(Contd. on page 3)



**Trade name: 39463 Undercoating**

(Contd. of page 2)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not gas tight seal receptacle.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

### 8052-42-4 Asphalt

REL	Short-term value: C 5* mg/m <sup>3</sup> fume; *15-min
TLV	0.5 I mg/m <sup>3</sup> as benzene-soluble aerosol

### 68476-86-8 Petroleum gases, liquefied, sweetened

TLV	Short-term value: 2950 mg/m <sup>3</sup> , 1000 ppm
-----	---

### 8052-41-3 Stoddard solvent

PEL	2900 mg/m <sup>3</sup> , 500 ppm
REL	Short-term value: C 1800* mg/m <sup>3</sup> Long-term value: 350 mg/m <sup>3</sup> *15-min
TLV	525 mg/m <sup>3</sup> , 100 ppm

### 108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	188 mg/m <sup>3</sup> , 50 ppm Skin; BEI

### 67-56-1 methanol

PEL	260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.

(Contd. on page 4)



**Trade name: 39463 Undercoating**

(Contd. of page 3)

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **General Information**

<b>Form:</b>	Aerosol
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	< -17°C (< 1°F)

· **Flash point:** < -17°C (< 1°F)

· **Ignition temperature:** 230.0°C (446°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:**

<b>Explosion limits:</b>	
<b>Lower:</b>	1.9 Vol %
<b>Upper:</b>	9.5 Vol %

· **Vapor pressure at 20°C (68°F):** 14.0 hPa (11 mm Hg)

· **Density at 20°C (68°F):** 0.78 g/cm<sup>3</sup>

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

(Contd. on page 5)



Trade name: 39463 Undercoating

(Contd. of page 4)

- **Solvent content:**
  - Organic solvents:** 52.9 %
  - VOC content:** 52.9 %  
397.2 g/l / 3.31 lb/gl
- **Solids content:** 47.1 %

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

### 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

### 12 Ecological information

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.

### 13 Disposal considerations

- **Product:**
- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 6)

Trade name: 39463 Undercoating

(Contd. of page 5)

## 14 Transport information

· DOT regulations:



- Hazard class: 2.1
- Identification number: UN1950
- Packing group: -
- Proper shipping name (technical name): AEROSOLS, flammable
- Label: 2.1

· Land transport ADR/RID (cross-border):



- ADR/RID class: 2 5F Gases
- Danger code (Kemler): 23
- UN-Number: 1950
- Packaging group: -
- Label: 2.1
- Description of goods: 1950 AEROSOLS

· Maritime transport IMDG:



- IMDG Class: 2.1
- UN Number: 1950
- Label: 2.1
- Packaging group: -
- EMS Number: F-D,S-U
- Marine pollutant: No
- Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label: 2.1
- Packaging group: -
- Proper shipping name: AEROSOLS, flammable

## 15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 7)



**Trade name: 39463 Undercoating**

(Contd. of page 6)

**· Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
67-56-1	methanol
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )

**· TSCA (Toxic Substances Control Act):**

8052-42-4	Asphalt
68476-86-8	Petroleum gases, liquefied, sweetened
64742-89-8	Solvent naphtha (petroleum), light aliph.
8052-41-3	Stoddard solvent
108-88-3	toluene
67-56-1	methanol
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )
1333-86-4	Carbon black

**· Proposition 65**

**· Chemicals known to cause cancer:**

8052-42-4	Asphalt
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1333-86-4	Carbon black

**· Chemicals known to cause reproductive toxicity:**

108-88-3	toluene
----------	---------

**· Cancerogenity categories**

**· EPA (Environmental Protection Agency)**

108-88-3	toluene	D
----------	---------	---

**· IARC (International Agency for Research on Cancer)**

8052-42-4	Asphalt	2B
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	TRACE AMOUNTS OF 14808-60-7
108-88-3	toluene	3
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
1333-86-4	Carbon black	2B

**· NTP (National Toxicology Program)**

None of the ingredients is listed.

**· TLV (Threshold Limit Value established by ACGIH)**

8052-42-4	Asphalt	A4
108-88-3	toluene	A4
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
1333-86-4	Carbon black	A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

8052-42-4	Asphalt
1333-86-4	Carbon black

**· OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**· Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 8)



**Trade name: 39463 Undercoating**

(Contd. of page 7)

· **Hazard symbols:**

Harmful  
Extremely flammable

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light aliph.  
Stoddard solvent  
Asphalt

· **Risk phrases:**

Extremely flammable.  
Harmful if swallowed.  
Irritating to eyes, respiratory system and skin.

· **Safety phrases:**

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).  
In case of insufficient ventilation, wear suitable respiratory equipment.  
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
Avoid exposure - obtain special instructions before use.

· **Special labeling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
52.9 % by mass of the contents are flammable  
Keep out of the reach of children.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Environment protection department.
- **Contact:** Mr. George Wallace