

# U-POL™

## SAFETY DATA SHEET

UP0719, UP0733 REFACE SPRAY FILLER

Page 1

Issued: 28/04/2004

Revision No: 6

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** UP0719, UP0733 REFACE SPRAY FILLER

**Product code:** UPOL SF

**Use / description of product:** PAINT PRODUCT CONTAINING STYRENE

**Company name:** U-Pol Products

US ADDRESS:

Sanders and Associates Inc.,

1263 Route 31 South

Lebanon

NJ 08833

USA

Fax: 1-800-787-5150

Emergency tel: 1-800-424-9300 (CHEMTREC)

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** STYRENE 10-30%

EINECS: 202-851-5 CAS: 100-42-5

[-] R10; [Xn] R20; [Xi] R36/38

- ETHYL ACETATE 1-10%

EINECS: 205-500-4 CAS: 141-78-6

[F] R11; [Xi] R36; [Xi] R66; [-] R67

### 3. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Harmful by inhalation. Irritating to eyes and skin.

**Other hazards:** May cause fire. May cause sensitisation by skin contact.

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

### 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

## 7. HANDLING AND STORAGE

**Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Hazardous ingredients:** STYRENE

TWA (8 hr exposure limit): 430 mg/m<sup>3</sup> STEL (15 min exposure limit): 1080 mg/m<sup>3</sup> (MEL)

- ETHYL ACETATE

TWA (8 hr exposure limit): 200 ppm STEL (15 min exposure limit): 400 ppm (OES)

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Compressed airline breathing apparatus (EN139).

**Hand protection:** Nitrile gloves.

**Eye protection:** Face-shield.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Liquid

**Colour:** Off-white

**Odour:** Astringent

**Evaporation rate:** Slow

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Viscosity value:** 5000 cps

**Flammability limits %:** lower: 1.1  
upper: 6.1  
**Flash point°C:** 21  
**Autoflammability°C:** 490  
**Relative density:** 1.65  
**VOC g/l:** 405

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat. Sources of ignition.

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** STYRENE  
IVN MUS LD50 90 mg/kg  
ORL MUS LD50 316 mg/kg  
ORL RAT LD50 2650 mg/kg

- ETHYL ACETATE  
ORL MUS LD50 4100 mg/kg  
ORL RAT LD50 5620 mg/kg  
SCU RAT LDLO 5 gm/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Heavier than water.

**Persistence and degradability:** Not biodegradable.

**Bioaccumulative potential:** No data available.

**Other adverse effects:** Harmful to aquatic organisms.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** D10 Incineration on land.  
R1 Solvent reclamation/regeneration.

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b> 1263	<b>ADR Class:</b> 3
<b>Packing group:</b> II	<b>Classification code:</b> F1
<b>Shipping name:</b> PAINT	
<b>Labelling:</b> 3	<b>Hazard ID no:</b> 33

**IMDG / IMO**

<b>UN no:</b> 1263	<b>Class:</b> 3
<b>Packing group:</b> II	<b>EmS:</b> F-E,S-E
<b>Marine pollutant:</b> .	<b>Labelling:</b> 3

**IATA / ICAO**

<b>UN no:</b> 1263	<b>Class:</b> 3
<b>Packing group:</b> II	<b>Packing instructions:</b> 305(P&CA); 307(CAO)
<b>Labelling:</b> 3	

**15. REGULATORY INFORMATION****Hazard symbols:** Harmful.**Risk phrases:** R10: Flammable.  
R20: Harmful by inhalation.  
R36/38: Irritating to eyes and skin.**Safety phrases:** S2: Keep out of the reach of children.  
S23 Do not breathe vapour/spray  
S51: Use only in well-ventilated areas.**VbF:** All**Water hazard class:** 1**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Risk phrases used in s.2:** R10: Flammable.  
R20: Harmful by inhalation.  
R36/38: Irritating to eyes and skin.  
R11: Highly flammable.  
R36: Irritating to eyes.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**SAFETY DATA SHEET**  
UP0719, UP0733 REFACE SPRAY FILLER

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.