

M A T E R I A L S A F E T Y D A T A S H E E T

I. IDENTIFICATION

MANUFACTURED FOR MEDCO
3201 South 76th Street
Philadelphia, PA 19153

REVISED: 07/02/2008
PRINTED: 07/08/2008

24 Hour Emergency Telephone
CHEMTREC 1-800-424-9300

General Information:
Mon-Fri 8 AM - 5 PM
712-737-4993

TRADE NAME: 1K ETCHING SATIN BLACK TRIM & BUMPER-AERO

MFG. PRODUCT NUMBER: 80061

II. HAZARDOUS INGREDIENTS

CAS #67-64-1	Acetone	WT %: 20-50	Footnote: (1)
	ACGIH TLV: 500 ppm TWA	ACGIH STEL: 1000 ppm	
	OSHA PEL: 1000 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 185mm Hg60F	LEL%: 2.6%	
CAS #75-28-5	Isobutane	WT %: 5-20	Footnote: (1)
	ACGIH TLV: N.E.	ACGIH STEL:	
	OSHA PEL: N.E.	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 3.1 atm	LEL%: 1.6	
CAS #74-98-6	Propane	WT %: 5-20	
	ACGIH TLV: 2500 ppm TWA	ACGIH STEL:	
	OSHA PEL: 1000 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 7150mmHg20c	LEL%:	
CAS #78-92-2	Secondary butanol	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 100 ppm TWA	ACGIH STEL:	
	OSHA PEL: 150 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 7mm Hg @ 50	LEL%:	
CAS #108-10-1	Methyl Isobutyl Ketone	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 50 ppm TWA	ACGIH STEL: 75 ppm	
	OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 15mm Hg20C	LEL%: 1.2	
CAS #1330-20-7	Xylene	WT %: 5-20	Footnote: (1)
	ACGIH TLV: 100 ppm	ACGIH STEL: 150 ppm	
	OSHA PEL: 100 ppm	OSHA CEILING: NE	OSHA PEAK: NE
	VAPOR PRESSURE: 7 mmHg@20C	LEL%: 1	
CAS #100-41-4	Ethyl Benzene	WT %: 1-5	
	ACGIH TLV: 100 ppm	ACGIH STEL: 125 ppm	
	OSHA PEL: 100 ppm	OSHA CEILING: NE	OSHA PEAK: NE
	VAPOR PRESSURE: 10 mmHg@20C	LEL%: 1	
CAS #111-76-2	Ethylene Glycol Butyl Ether	WT %: 1-5	Footnote: (1)
	ACGIH TLV: 20 ppm TWA SKIN	ACGIH STEL:	
	OSHA PEL: 50 PPM TWA SKIN	OSHA CEILING:	OSHA PEAK:
	VAPOR PRESSURE: 0.9 mm	LEL%: 1.1	
CAS #67-63-0	Isopropyl Alcohol	WT %: 1-5	Footnote: (1)
	ACGIH TLV: 400 ppm TWA	ACGIH STEL: 500 ppm TWA	
	OSHA PEL: 400 ppm TWA	OSHA CEILING:	OSHA PEAK:

VAPOR PRESSURE: 33 mm

LEL%: 2.0

WARNING MESSAGES:

- (1) Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys, and blood.
- (2) See Section IX for reportable Hazardous Air Pollutants.

III. PHYSICAL DATA

BOILING RANGE: -43-340° F

EVAPORATION RATE: Propellant: Faster than ether Solvent: Slower than ether.

PERCENT VOLATILE BY VOLUME: 91.40% WEIGHT PER GALLON: 6.38 LBS

VAPOR DENSITY: Propellant is lighter than air Solvent is heavier than air

ACTUAL VOC (lb/gal): 2.92

EPA VOC (lb/gal): 4.72

EPA VOC (g/L): 565.64

IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -156° F -105° C LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: CLASS 1A

HAZARD CLASSIFICATION: FLAMMABLE CONSUMER COMMODITY ORM-D

EXTINGUISHING MEDIA: *carbon dioxide, dry chemical, or fire foam*

UNUSUAL FIRE AND EXPLOSION HAZARDS: With excessive heat, cans will rupture from internal pressure and discharge flammable contents. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors to achieve cross-ventilation.

SPECIAL FIRE FIGHTING PROCEDURES:

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible

autoignition or explosion when exposed to extreme heat.

V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVEREXPOSURE:

Inhalation - Anesthetic

Irritation of the respiratory tract or acute nervous system. Depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness or coma.

Acute - High vapor concentrations are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects including death. Product has a low order of acute oral and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possible death.

Chronic - Xylene contains ethylbenzene which has been classified as a possible carcinogen to humans, Group 2B, by the International Agency for Research on Cancer (IARC), based on sufficient evidence in laboratory animals but inadequate evidence for cancer in humans. Prolonged or repeated overexposure to ethylbenzene may cause the following effects: kidney effects, liver effects, lung effects, thyroid effects, testicular effects, pituitary effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Eye disease, Skin disorders and Allergies

PRIMARY ROUTE(S) OF ENTRY: Eyes, Ingestion, Skin, Inhalation

EMERGENCY AND FIRST AID PROCEDURES: Inhalation - Remove to fresh air.

Eyes - Flush immediately with fresh water for 15 minutes.

Call a physician.

Skin- Wash thoroughly with soap and water

VI. REACTIVITY DATA

STABILITY: *stable*

HAZARDOUS POLYMERIZATION: *will not occur*

INCOMPATIBILITY: oxidizing agents, halogens, strong reducing agents and strong bases.

HAZARDOUS DECOMPOSITION: When heated to decomposition, toxic fumes are formed.

CONDITIONS TO AVOID: Fire, burning, and welding.

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbant.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not incinerate closed containers.

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: For casual use none required. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Avoid contact with eyes, skin and clothing.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: Permeation resistant gloves (butyl rubber, nitrile rubber) should be used. Cover as much of the exposed skin area as possible with appropriate clothing.

EYE PROTECTION:

Splash proof eye goggles. In emergency situations, use eye goggles with a full face shield.

OTHER PROTECTIVE EQUIPMENT: Protective clothing such as coveralls or lab coats must be worn.

HYGIENIC PRACTICES: See Section V

IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 120 degrees F. Store large quantities in buildings designed and protected for storage of NFPA Class 1A flammable liquids.

OTHER PRECAUTIONS: Do not spray in eyes. Do not puncture or incinerate cans. Do not stick pin or any sharp objects into opening on top of can. Finger must not protrude over

spray button.

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Ingredient	CAS #	Wt% of HAPS in product	Pounds HAPS/ Gal product
Methyl Isobutyl Ketone	108-10-1	7.1 %	0.5
Xylene	1330-20-7	5.5 %	0.4
Ethyl Benzene	100-41-4	1.2 %	0.1
