Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M(TM) Flowable Finishing Putty, P.N. 05823, 05824
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 01/26/2006
Supercedes Date: 08/02/2004

Document Group: 06-7851-6

ID Number(s):

60-9800-2271-3, 60-9800-2651-6, 60-9800-3544-2

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

06-6914-3, 06-7098-4

Reason for Reissue: The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes:
Copyright was modified.
Kit: Component document group number(s) was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) Creme Hardener - PN 05313, 05828, 05829, 05830, 05831, 05852, 05853
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 12/19/2006
Supercedes Date: 10/02/2006

Document Group: 06-6914-3

Product Use:
Intended Use: Automotive
Specific Use: Catalyst for Automotive Body Fillers

SECTION 2: INGREDIENTS

Ingredient	C.A.S. No.	% by Wt
BENZOYL PEROXIDE	94-36-0	30 - 60
WATER	7732-18-5	10 - 30
BENZOIC ACID, C9-11-BRANCHED ALKYL ESTERS	131298-44-7	10 - 20
ZINC STEARATE	557-05-1	3 - 7
OXIRANE, POLYMER WITH METHYLOXIRANE, MONOBUTYL ETHER	9038-95-3	3 - 7
CALCIUM SULFATE	7778-18-9	1 - 5
IRON OXIDE (FE2O3)	1309-37-1	1 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Viscous
Odor, Color, Grade: Red paste with slight ester odor
General Physical Form: Solid
Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Dust clouds of this material in combination with an ignition source may be explosive. May cause allergic skin reaction.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:
Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of cold water for at least 15 minutes. If signs/symptoms develop, get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	*No Data Available*
Flash Point	*Not Applicable*
Flammable Limits - LEL	*Not Applicable*
Flammable Limits - UEL	*Not Applicable*

5.2 EXTINGUISHING MEDIA

Water from a safe distance - preferably with a fog nozzle. In case of small fires, other means such as carbon dioxide, foam or dry chemical extinguishers may be effective.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Closed containers exposed to heat from fire may build pressure and explode. Dust clouds of this material in combination with an ignition source may be explosive. Fire hazard increases when material becomes dry. Part of the oxygen for combustion is supplied by the peroxide itself.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with water. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid eye contact with dust or airborne particles.

7.2 STORAGE

Store away from heat. Store out of direct sunlight. Keep container tightly closed. Do not heat under confinement to avoid risk of explosion Storage at elevated temperatures will shorten shelf life.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust for cutting, grinding, sanding or machining. Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.
The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.
Gloves made from the following material(s) are recommended: Butyl Rubber, Fluoroelastomer (Viton).

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining.
Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters.
Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

Ingredient	Authority	Type	Limit	Additional Information
BENZOYL PEROXIDE	ACGIH	TWA	5 mg/m3	Table A4
BENZOYL PEROXIDE	OSHA	TWA	5 mg/m3	Table Z-1
CALCIUM SULFATE	ACGIH	TWA, inhalable fraction	10 mg/m3	
CALCIUM SULFATE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
CALCIUM SULFATE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
IRON OXIDE (FE2O3)	ACGIH	TWA, respirable	5 mg/m3	Table A4
IRON OXIDE (FE2O3)	OSHA	TWA, as fume	10 mg/m3	Table Z-1A
STEARATES	ACGIH	TWA, as total dust	10 mg/m3	Table A4
ZINC STEARATE	ACGIH	TWA	10 mg/m3	
ZINC STEARATE	ACGIH	STEL	20 mg/m3	
ZINC STEARATE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
ZINC STEARATE	OSHA	TWA, Vacated, as dust	10 mg/m3	
ZINC STEARATE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1

VAC Vacated PEL:Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA:
ACGIH: American Conference of Governmental Industrial Hygienists
CMRG: Chemical Manufacturer Recommended Guideline
OSHA: Occupational Safety and Health Administration
AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Viscous
Odor, Color, Grade:	Red paste with slight ester odor
General Physical Form:	Solid

Autoignition temperature	*No Data Available*
Flash Point	*Not Applicable*
Flammable Limits - LEL	*Not Applicable*
Flammable Limits - UEL	*Not Applicable*
Boiling point	[*Details:* Decomposes]
Density	*No Data Available*
Vapor Density	*Not Applicable*
Vapor Pressure	*Not Applicable*
Specific Gravity	1.2 [@ 25 ºC] [*Ref Std:* WATER=1]
pH	*No Data Available*
Melting point	*No Data Available*
Solubility in Water	Negligible
Evaporation rate	*Not Applicable*
Hazardous Air Pollutants	0 % weight
Volatile Organic Compounds	0 lb/gal [*Test Method:* calculated SCAQMD rule 443.1] [*Details:* excluding exempt compounds]
Percent volatile	20 % [*Details:* Water is the volatile component]
VOC Less H2O & Exempt Solvents	0 g/l [*Test Method:* calculated SCAQMD rule 443.1]
Viscosity	*No Data Available*

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable. Stable unless exposed to heat, flames and drying conditions.

Materials and Conditions to Avoid: Accelerators, dimethylaniline, cobalt napthenate and other promoters, reducing agents, or any hot materials. Additional Information: Storage at elevated temperatures will shorten shelf life.

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):
LB-K100-0053-7, LB-K100-0053-8, LB-K100-0053-9, 60-9800-2274-7, 60-9800-2275-4, 60-9800-2289-5, 60-9800-2305-9, 60-9800-2848-8, 60-9800-2849-6, 60-9800-3016-1, 60-9800-3017-9, 60-9800-3050-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS
Contact 3M for more information.

311/312 Hazard Categories:
Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
BENZOYL PEROXIDE	94-36-0	30 - 60
ZINC STEARATE (ZINC COMPOUNDS)	557-05-1	3 - 7

STATE REGULATIONS
Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 **Flammability:** 2 **Reactivity:** 1 **Special Hazards:** Oxidizer

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:
Section 1: Product use information was modified.
Section 9: Property description for optional properties was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) Flowable Finishing Putty - P.N. 05823, 05824, 05851, 05798
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/02/2006
Supercedes Date: 09/29/2006

Document Group: 06-7098-4

Product Use:
Limitations on Use: This product is to be used with 3M(TM) Creme Hardener, P/N 05828, 05829, 05830, or 05831.
Specific Use: Automotive Body Putty

SECTION 2: INGREDIENTS

Ingredient	C.A.S. No.	% by Wt
TALC	14807-96-6	20 - 40
STYRENE MONOMER	100-42-5	10 - 30
Unsaturated Polyester Resin 2	Trade Secret	10 - 30
LIMESTONE	1317-65-3	10 - 20
TITANIUM DIOXIDE	13463-67-7	1 - 10
SILICA	7631-86-9	1 - 10
GLASS BUBBLES	65997-17-3	1 - 10
Unsaturated Polyester Resin 1	Trade Secret	5 - 10
MAGNESIUM CARBONATE	546-93-0	1 - 5
TRIMETHYLOLPROPANE TRIACRYLATE	15625-89-5	1 - 5
TRIETHYL PHOSPHATE	78-40-0	<= 0.6
COBALT OCTOATE	136-52-7	< 0.5
QUARTZ SILICA	14808-60-7	< 0.5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste
Odor, Color, Grade: Light yellow with styrenic odor
General Physical Form: Liquid
Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause allergic skin reaction. May cause allergic respiratory reaction. May cause target organ effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

May be absorbed through skin and cause target organ effects.

Inhalation:
Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

During grinding, scraping, sanding:
Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

May be absorbed following inhalation and cause target organ effects.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:
Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:
Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
COBALT COMPOUNDS	NONE	Group 2B	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Group 1	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
STYRENE MONOMER	100-42-5	Group 2B	International Agency for Research on Cancer

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	*No Data Available*
Flash Point	88.0 ºF
Flammable Limits - LEL	*No Data Available*
Flammable Limits - UEL	*No Data Available*

5.2 EXTINGUISHING MEDIA
Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Water may be used to blanket the fire. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition

information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid static discharge. Keep out of the reach of children. Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe vapors. Do not breathe dust. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Store away from oxidizing agents. Store away from strong bases.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust for cutting, grinding, sanding or machining. Do not use in a confined area or areas with little or no air movement.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. Avoid eye contact with vapors, mists, or spray.
The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.
Gloves made from the following material(s) are recommended: Polyvinyl Alcohol (PVA), Polyethylene/Ethylene Vinyl Alcohol.

8.2.3 Respiratory Protection
Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe vapors. Do not breathe dust.
Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters.
Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing
Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Not applicable.

8.3 EXPOSURE GUIDELINES

Ingredient	Authority	Type	Limit	Additional Information
COBALT COMPOUNDS	ACGIH	TWA, as Co	0.02 mg/m3	Table A3
LIMESTONE	ACGIH	TWA	10 mg/m3	
LIMESTONE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
LIMESTONE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
MAGNESIUM CARBONATE	ACGIH	TWA	10 mg/m3	
MAGNESIUM CARBONATE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
MAGNESIUM CARBONATE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
GLASS BUBBLES	3M	TWA, as dust	10 mg/m3	
QUARTZ SILICA	ACGIH	TWA, respirable	0.025 mg/m3	Table A2
QUARTZ SILICA	OSHA	TWA, respirable	0.1 mg/m3	Table Z-1A
SILICA	CMRG	TWA, as respirable dust	3 mg/m3	
STYRENE MONOMER	ACGIH	TWA	20 ppm	Skin Notation*; Table A4
STYRENE MONOMER	ACGIH	STEL	40 ppm	Skin Notation*; Table A4
STYRENE MONOMER	OSHA	TWA, Vacated	50 ppm	
STYRENE MONOMER	OSHA	TWA	100 ppm	Table Z-2
STYRENE MONOMER	OSHA	STEL, Vacated	100 ppm	
STYRENE MONOMER	OSHA	CEIL	200 ppm	Table Z-2
TALC	ACGIH	TWA, respirable	2 mg/m3	Table A4
TALC	CMRG	TWA, as respirable dust	0.5 mg/m3	
TALC	OSHA	TWA, respirable	2 mg/m3	Table Z-1A
TITANIUM DIOXIDE	ACGIH	TWA	10 mg/m3	Table A4
TITANIUM DIOXIDE	CMRG	TWA, as respirable dust	5 mg/m3	
TITANIUM DIOXIDE	OSHA	TWA, Vacated, as dust	10 mg/m3	
TITANIUM DIOXIDE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1
TRIMETHYLOLPROPANE TRIACRYLATE	AIHA	TWA	1 mg/m3	
ZIRCONIUM COMPOUNDS	ACGIH	TWA, as Zr	5 mg/m3	Table A4
ZIRCONIUM COMPOUNDS	ACGIH	STEL, as Zr	10 mg/m3	Table A4
ZIRCONIUM COMPOUNDS	OSHA	TWA, as Zr	5 mg/m3	Table Z-1A
ZIRCONIUM COMPOUNDS	OSHA	STEL, as Zr	10 mg/m3	Table Z-1A

* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL:Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA:
ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline
OSHA: Occupational Safety and Health Administration
AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Light yellow with styrenic odor
General Physical Form:	Liquid
Autoignition temperature	*No Data Available*
Flash Point	88.0 ºF
Flammable Limits - LEL	*No Data Available*
Flammable Limits - UEL	*No Data Available*
Boiling point	293.00 ºF [*Details:* CONDITIONS: (Styrene)]
Vapor Density	3.60 [*Ref Std:* AIR=1] [*Details:* CONDITIONS: (Styrene)]
Vapor Pressure	4.3000 mmHg [*Details:* CONDITIONS: at 20 C (Styrene)]
Specific Gravity	1.10 [*Ref Std:* WATER=1]
pH	*No Data Available*
Melting point	*No Data Available*
Solubility in Water	Nil
Evaporation rate	*No Data Available*
Volatile Organic Compounds	2.14 lb/gal [*Test Method:* calculated SCAQMD rule 443.1] [*Details:* excluding exempt compounds]
Percent volatile	23.35 % [*Details:* excluding exempt compounds]
VOC Less H2O & Exempt Solvents	256.96 g/l [*Details:* excluding exempt compounds]
Viscosity	70000.0 - 150000.0 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong acids; Strong bases; Strong oxidizing agents Additional Information: Storage at elevated temperatures will shorten shelf life.

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Styrene Oxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

Hazardous Decomposition: Normal use of this product can generate styrene oxide (CAS No. 96-09-3). Styrene oxide is listed as a Group 2A carcinogen by IARC and is listed as a carcinogen in the California Proposition 65 regulations.

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

LB-K100-0115-9, LB-K100-0116-0, LB-K100-0116-1, LB-K100-0115-8

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
STYRENE MONOMER	100-42-5	10 - 30
COBALT OCTOATE (COBALT COMPOUNDS)	136-52-7	< 0.5

STATE REGULATIONS
Contact 3M for more information.

CALIFORNIA PROPOSITION 65

Ingredient	C.A.S. No.	Classification
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	NONE	**Carcinogen

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES
The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

Additional Information: This product is to be used with 3M Creme Hardener, P/N 05828, 05829, 05830, or 05831.

INTERNATIONAL REGULATIONS
Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 **Flammability:** 3 **Reactivity:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:
Section 16: Reason for reissue heading was deleted.
Section 16: Reason for reissue phrase was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.