

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *M25(xx)3 Series Marine Vinyl Coat*
- **Article number:**  
*M25003, M25013, M25023, M25033, M25043, M25053, M25063, M25073, M25083, M25093, M25103, M25113, M25123, M25133, M25143, M25153, M25163, M25173, M25183, M25193, M25203, M25213, M25223, M25233, M25243*
- **Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the preparation** *Not applicable*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225*
- **Information department:**  
*cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT*
- **Emergency telephone number:** *24 HR EMERGENCY CHEMTREC 1-800-424-9300*

## 2 Hazards identification

- **Classification of the substance or mixture**



**GHS02 Flame**

*Flam. Aerosol 1 H222 Extremely flammable aerosol.*



**GHS08 Health hazard**

*Repr. 2 H361 Suspected of damaging fertility or the unborn child.*

*STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.*



**GHS07**

*Skin Irrit. 2 H315 Causes skin irritation.*

*Eye Irrit. 2A H319 Causes serious eye irritation.*

*STOT SE 3 H336 May cause drowsiness or dizziness.*

- **Label elements**

- **GHS label elements** *The product is classified and labelled according to the Globally Harmonized System (GHS).*

- **Hazard pictograms** *GHS02, GHS07, GHS08*

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

*toluene*

- **Hazard statements**

*H222 Extremely flammable aerosol.*

(Contd. on page 2)

**Trade name: M25(xx)3 Series Marine Vinyl Coat**

(Contd. of page 1)

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	30 - 40%
68476-86-8	Petroleum gases, liquefied, sweetened ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280	13 - 30%
108-88-3	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10 - 13%
	ACRYLIC RESIN ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336	7 - 10%
110-19-0	isobutyl acetate ⚠ Flam. Liq. 2, H225	1.5 - 5%

(Contd. on page 3)

Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 2)

108-10-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	1.5 - 5%
78-93-3	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1.5 - 5%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-1.5%
2807-30-9	2-(propyloxy)ethanol ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Eye Irrit. 2, H319	1-1.5%
67-56-1	methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370	≤1%

#### 4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 3)

See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 67-64-1 acetone

PEL ()	2400 mg/m <sup>3</sup> , 1000 ppm
REL ()	590 mg/m <sup>3</sup> , 250 ppm
TLV ()	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m <sup>3</sup> , (500) NIC-200 ppm BEI

### 108-88-3 toluene

PEL ()	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL ()	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV ()	75 mg/m <sup>3</sup> , 20 ppm BEI

### 110-19-0 isobutyl acetate

PEL ()	700 mg/m <sup>3</sup> , 150 ppm
--------	---------------------------------

(Contd. on page 5)



Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 4)

REL ()	700 mg/m <sup>3</sup> , 150 ppm
TLV ()	713 mg/m <sup>3</sup> , 150 ppm
<b>108-10-1 4-methylpentan-2-one</b>	
PEL ()	410 mg/m <sup>3</sup> , 100 ppm
REL ()	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV ()	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI
<b>78-93-3 butanone</b>	
PEL ()	590 mg/m <sup>3</sup> , 200 ppm
REL ()	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV ()	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm BEI
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEEL ()	50 ppm
<b>67-56-1 methanol</b>	
PEL ()	260 mg/m <sup>3</sup> , 200 ppm
REL ()	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV ()	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI
<b>Ingredients with biological limit values:</b>	
<b>67-64-1 acetone</b>	
BEI ()	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
<b>108-88-3 toluene</b>	
BEI ()	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 6)

Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 5)

<b>108-10-1 4-methylpentan-2-one</b>	
BEI ( )	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
<b>78-93-3 butanone</b>	
BEI ( )	2 mg/L Medium: urine Time: end of shift Parameter: MEK
<b>67-56-1 methanol</b>	
BEI ( )	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· Flash point: -103 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 465 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:	1.2 Vol %
Upper:	13.0 Vol %

· Vapor pressure at 20 °C: 233 hPa

· Density at 20 °C: 0.8111 g/cm<sup>3</sup>

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents: 87.3 %

(Contd. on page 8)





Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 7)

<b>VOC content:</b>	19.5 % 444.2 g/l / 3.71 lb/gl
<b>Solids content:</b>	12.7 %
<b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

USA

(Contd. on page 9)



Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 8)

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |                                  |                     |
|----------------------------------|---------------------|
| · <b>UN-Number</b>               |                     |
| · <b>DOT, ADR, IMDG, IATA</b>    | UN1950              |
| · <b>UN proper shipping name</b> |                     |
| · <b>DOT, IATA</b>               | AEROSOLS, flammable |
| · <b>ADR</b>                     | 1950 AEROSOLS       |
| · <b>IMDG</b>                    | AEROSOLS            |

· **Transport hazard class(es)**

· **DOT**



- |                |     |
|----------------|-----|
| · <b>Class</b> | 2.1 |
| · <b>Label</b> | 2.1 |

(Contd. on page 10)

Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 9)

· ADR



· Class 2 5F Gases  
· Label 2.1

· IMDG, IATA



· Class 2.1  
· Label 2.1

· Packing group  
· DOT, ADR, IMDG, IATA Void

· Environmental hazards:  
· Marine pollutant: No

· Special precautions for user Warning: Gases  
· EMS Number: F-D,S-U

· Transport in bulk according to Annex II of  
MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

**15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture  
· Sara

· Section 355 (extremely hazardous substances):  
None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3	toluene
	ACRYLIC RESIN
108-10-1	4-methylpentan-2-one
78-93-3	butanone
67-56-1	methanol
1330-20-7	xylene
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
68476-86-8	Petroleum gases, liquefied, sweetened
108-88-3	toluene

(Contd. on page 11)



Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 10)

110-19-0	isobutyl acetate
108-10-1	4-methylpentan-2-one
78-93-3	butanone
763-69-9	ethyl 3-ethoxypropionate
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
13463-67-7	titanium dioxide
1333-86-4	Carbon black
51274-00-1	YELLOW IRON OXIDE
67-56-1	methanol
1332-37-2	Iron oxide
7631-86-9	silicon dioxide, chemically prepared

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
108-10-1	4-methylpentan-2-one	I
78-93-3	butanone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black

(Contd. on page 12)



Trade name: M25(xx)3 Series Marine Vinyl Coat

(Contd. of page 11)

67-56-1 | methanol

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labelled according to the Globally Harmonized System (GHS).

· **Hazard pictograms** GHS02, GHS07, GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene

· **Hazard statements**

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent