LORD USER INSTRUCTIONS

LORD Fusor® 121/124 Flexible Foam

(Super Fast)

LORD Fusor® 121/124 flexible foam can be used for sound deadening, sealing and filling of door skins to crash bar, hood panel to supports, trunk panel to supports and gas tank filler area.

Usage

- Remove any necessary panels and use a drop cloth to protect the surrounding area against accidental drippage.
- Remove cap from the LORD Fusor 121/124 flexible foam cartridge and cut off the end of the cartridge tip.
- 3. Insert the cartridge into a manual dispensing gun. Note: Due to the thin viscosity of the material, a pneumatic gun is not recommended.
- Gently squeeze out a small amount of material to ensure that foam freely flows from both ends of the tube.
- 5. Attach the mixing tip.
- 6. Apply a bead of LORD Fusor 121/124 flexible foam between the vibrating panels (see Illustration A).
- 7. Avoid dispensing material too quickly. Foam will expand approximately 10 times its original volume to fill voids or eliminate vibration.
- When sealing pillars or posts, apply a sufficient amount of LORD Fusor 121/124 flexible foam; approximately 1/3 of a cartridge may be needed depending on size and configuration of void.
- Remove the mixing tip immediately after usage and install supplied cartridge plugs to avoid pressure build-up.
- 10. If desired, LORD Fusor 121/124 flexible foam can be painted in 10 minutes.

Technical Tip

When applying LORD Fusor 121/124 flexible foam to a vertical panel, dispense the material to the end of the tip. Allow the material to start foaming, then slowly dispense into the appropriate area. This will keep the material from running down the panel.

Technical Data


Work (Expansion) Time, seconds @ 70°F (21°C)	5-10
Full Cure Strength, hours @ 70°F (21°C)	1
Handling Strength (Full Expansion), minutes	
@ 70°F (21°C)	2-3
Paintability, minutes @ 70°F (21°C)	10

Cautionary Information

Before using this or any LORD product, refer to the Material Safety Data Sheet (MSDS) and label for safe use and handling instructions.

For industrial/commercial use only. Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

Illustration A





LORD USER INSTRUCTIONS

LORD Fusor Repair Products Lifetime Guarantee*

LORD Corporation guarantees to the original purchaser that LORD Fusor® Repair Products (adhesives, primers, seam sealers and foams only), when used in strict accordance with LORD Corporation's application and use instructions, will provide a durable bond for the life of the vehicle. This Guarantee covers actual costs incurred by the installer for labor, replacement parts and materials, and for the reasonable cost of loss of use of the vehicle during the period of replacement. THIS GUARANTEE IN NOT APPLICABLE TO APPLICATION EQUIPMENT, INCLUDING BUT NOT LIMITED TO DISPENSING EQUIPMENT, CARTRIDGE TIPS AND ACCESSORIES.

THIS EXPRESS WARRANTY IS MADE IN LIEU OF AND EXCLUDES ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

LORD Corporation shall not be liable under any circumstance for any loss, damage, or expense directly or indirectly arising from the application and use of LORD Fusor Products sold hereunder or from any other cause, and LORD Corporation shall not be liable under any circumstances for consequential or incidental damages. LORD CORPORATION'S LIABILITY FOR BREACH OF WARRANTY HEREUNDER IS IN ALL INSTANCES LIMITED SOLELY AND EXCLUSIVELY TO THE REASONABLE COSTS OF REPAIR AND/OR REPLACEMENT OF THE BONDED METAL COMPONENTS OF THE VEHICLE.

This Lifetime Guarantee shall only apply to the above listed LORD Fusor products sold by LORD Corporation on or after January 1, 2001.

LORD Fusor Metal Bonding Adhesives shall only be used for bonding metal to metal (steel or aluminum) in full or partial panel replacements of:

- door skins
- roof skins
- other outer body sheet metal

- quarter panels
- rear body panels

LORD Fusor products SHALL NOT be used for bonding structural components such as rails, pillars, rocker panels, core supports, etc. If in doubt as to what is a structural component, contact the vehicle manufacturer. If you have any questions or need to receive proper use instructions, contact the LORD Customer Support Center at +1 877 ASK LORD (275 5673) or visit www.lord.com.

To comply with the requirements of the LORD Fusor Repair Products Lifetime Guarantee, attach a copy of this completed page to the repair record, and retain with your files:

Vehicle Make/Model:

Vehicle Identification Number:

LORD Fusor Product(s) Used for Repair:

Lot Number(s) on Cartridge(s) Used for Repair:

*This guarantee is void if adhesive is used after the date printed on the cartridge label





Instructions contained in this document need to be followed to qualify for the LORD Fusor Lifetime Guarantee. Values stated in these instructions represent typical values as not all tests are run on each lot of material produced. For formalized product specifications for specific product end uses, contact the Customer Support Center.

Information provided herein is based upon tests believed to be reliable. In as much as LORD Corporation has no control over the manner in which others may use this information, it does not guarantee the results to be obtained. In addition, LORD Corporation does not guarantee the performance of the product or the results obtained from the use of the product or this information where the product has been repackaged by any third party, including but not limited to any product end-user. Nor does the company make any express or implied warranty of merchantability or fitness for a particular purpose concerning the effects or results of such use.

Fusor and "Ask Us How" are trademarks of LORD Corporation or one of its subsidiaries. I-CAR and Industry Training Alliance are registered trademarks of Inter-Industry Conference on Auto Collision Repair. ASE is a registered trademark of the National Institute for Automotive Service Excellence.

LORD provides valuable expertise in adhesives and coatings, vibration and motion control, and magnetically responsive technologies. Our people work in collaboration with our customers to help them increase the value of their products. Innovative and responsive in an ever-changing marketplace, we are focused on providing solutions for our customers worldwide ... Ask Us How.

LORD Corporation World Headquarters

111 Lord Drive Cary, NC 27511-7923 USA

Customer Support Center (in United States & Canada) +1 877 ASK LORD (275 5673)

www.lord.com

For a listing of our worldwide locations, visit LORD.com.

LORD
AskUsHow