

**Finish Pro
5100****SAFETY DATA SHEET****Section 1: IDENTIFICATION OF THE MIXTURE AND OF THE SUPPLIER**

Product Name: Cumberland Products CP-10

Product Code: B10440

MSDS Date: September 16, 2013

Cumberland Products Inc

50 Commerce Parkway

Hodgenville, KY 42748

Phone: 800.223.1918 / Fax800.500.9812

Chemtrec (USA): 800.424.9300 For Emergencies

Section 2: HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****GHS Classification:**

Flammable liquids, Category 2

Acute toxicity Oral, Category 4

Acute toxicity Inhalation Category 4

Acute toxicity Dermal Category 4

Skin Irritation, Category 2

Eye irritation, Category 2A

Toxic to reproduction, Category 2

Specific target organ toxicity following single exposure, Category 3

Specific target organ toxicity – single exposure Category 1

Aspiration hazard, Category 1

GHS Labeling

Symbol:

Signal Word: Danger

Hazard Statements:

Highly flammable liquid and vapor

Harmful if swallowed

Harmful in contact with skin.

Harmful if inhaled.

Causes skin and serious eye irritation

Suspected of damaging fertility or the unborn child

Causes damage to organs.

May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Precautionary Statements:**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Wear protective gloves/protective clothing.
Avoid breathing mist/vapors/spray.
Wash hands thoroughly after handling.
Do not eat, drink, or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not handle until all safety precautions have been read and understood.
Obtain special instructions before use.
Do not breath mist/vapor/spray.
Use only outdoors or in well-ventilated area.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash skin with plenty of water/shower.
In case of fire: consider carbon dioxide, dry chemical powder, dry sand, limestone powder, or alcohol resistant foam to extinguish.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
If skin irritation occurs: Get medical advice/attention.
If exposed or concerned: Get medical advice/attention.
Rinse mouth
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor/medical advice/attention if you feel unwell.

Storage:

Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects: See Section 11 for more information

This product does not contain carcinogens or potential carcinogens as listed by IARC, NTP, or ACGIH.

This material contains components that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Environmental Effects: See Section 12 for more information.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

No.	Component CAS REG. NO.	Amount %	OSHA		ACGIH	
			TWA	STEL	TWA	STEL
1	Methanol CAS #67-56-1	1-100	Not avail	Not avail	200 ppm	250 ppm
2	Toluene CAS #108-88-3	1-100	200 ppm	Not Avail	20 ppm	Not Avail
3	Light Hydrotreated Distillate 68410-97-9	1-100	5 mg/m ³	Not avail	5 mg/m ³	Not avail

4	Acetone 67-64-1	1-100	1,000 ppm	Not Avail	500 ppm	Not Avail
---	--------------------	-------	--------------	--------------	------------	--------------

Section 4: FIRST AID MEASURES

Emergency first aid procedures by route of exposure:

- Inhalation:** If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion:** Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Medical care must emphasize the control of acidosis and the use of intravenous bicarbonate has been lifesaving. Evidence is good that treatment of methanol absorption is enhanced through the administration of ethanol, which should be given to produce a blood level of at least 0.1%. Ethanol diminishes the production of toxic metabolites of methanol. Blood methanol level of 50 mg/100mL is an indication for hemodialysis, which has improved the prognosis of methanol intoxication. Methanol is often confused with beverage alcohol (ethylalcohol). Care must be taken to prevent its ingestion, the most frequent cause of methanol poisoning. Prevent aspiration of vomit. Turn victim's head to the side. Do not induce vomiting. If the material is swallowed, get medical attention or advice.
- Skin:** Wash off for 20 minutes. Remove contaminated clothing, and any extraneous chemical.
- Eyes:** Immediately flush eyes with water for at least 20 minutes while holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

Note to physician: In case of ingestion or massive inhalation, observe victim as an inpatient because of slow metabolism causes latent period of 24 hours between exposure and acidosis and blindness.

Section 5: FIRE FIGHTING MEASURES

Flash Point (toluene): Closed cup: 4°C (39°F). (Tagliabue (ASTM D-56))

Auto-ignition Temperature (toluene): 536°C (997°F)

Lower Explosion Limit (toluene): AP 1.2 %

Upper Explosion Limit (toluene): AP 7.1 %

Flammability Classification: Flammable Liquid Class IB

Suitable Extinguishing Media:

Use methods appropriate for the surrounding fire. Consider carbon dioxide, dry chemical powder, dry sand, limestone powder, or alcohol resistant foam.

Products of Combustion: Upon decomposition this product may emit carbon dioxide, carbon monoxide, and/or low molecular weight hydrocarbons.

Fire Fighting Equipment/Instructions:

Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self-contained breathing apparatus for fire-fighting if necessary

HAZARD	HMIS	NFPA
Toxicity	3	3
Fire	3	3
Reactivity	0	0

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Protection: For large spills wear gloves, Tyvek suits, safety glasses, and appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

Special Properties: Flammable Liquid! This material releases vapors at or below ambient temperatures. When mixed with air in certain proportions and exposed to an ignition source, its vapor can cause a flash fire. Use only with adequate ventilation. Vapors are heavier than air and may travel long distances along the ground to an ignition source and flash back. A vapor and air mixture can create an explosion hazard in confined spaces such as sewers. If container is not properly cooled, it can rupture in the heat of a fire.

Environmental Precautions: Prevent discharge to open bodies of water, municipal sewers, and watercourses.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth. Control runoff and isolate discharged material for proper disposal. Approach release from upwind.

Methods for Clean-up: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container.

Section 7: HANDLING AND STORAGE

Handling:

Keep away from heat, sparks and flame. Use only with adequate ventilation.

To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

Storage:

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Keep away from oxidizers.

Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protective Equipment (PPE)

Respiratory Protection: Wear appropriate respirator when ventilation is inadequate.

Eye/Face Protection: Splash proof chemical goggles and face shield.

Hand Protection: Neoprene gloves, impervious gloves, the breakthrough time of the selected glove(s) must be greater than the intended use period.

Body: Avoid skin contact. If product comes in contact with clothing, immediately remove soaked clothing and shower. Wear long sleeve shirts and trousers without cuffs.

Other Protective Equipment:

Facilities storing or utilizing this material should be equipped with eyewash and safety shower facilities.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance, State	Clear liquid
Color	Colorless
Odor	Not available
pH (1%soln/water)	Not Available
Vapor Density (toluene)	>3 (Air=1)

Boiling Range (toluene)	80 to 145°C (176 to 293°F)
Vapor Pressure (toluene)	AP 3.2 kPa (AP 24 mm Hg) (at 20°C)
Melting Point	Not Available
Freezing Point	Not Available
Flash Point (See Section 5)	
Flammability Properties (See section 5)	
Solubility (in water)	Very Slightly Soluble
Specific Gravity (toluene)	0.87 (Water = 1)
Evaporation Rate	Not Available
Octanol/Water partition coefficient (K_{ow})	Not Available
Auto-ignition temperature:	Not Available
Decomposition temperature:	Not Available

Section 10: STABILITY AND REACTIVITY

Stability: This material is considered stable at ambient temperatures 70°C (21°C).

Condition to Avoid: Flames, sparks, electrostatic discharge, heat and other ignition sources.

Incompatible Materials: This product reacts with strong acid, strong bases, and oxidizing agents.

Hazardous Decomposition: Upon decomposition, this product evolves carbon monoxide, carbon dioxide, and/or low weight hydrocarbons.

Hazardous Reactions: This product will not undergo polymerization.

Section 11: TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

Component Analysis LD50

Methanol (67-56-1)

LD₅₀: Oral, Mouse - 7300 mg/Kg

LD₅₀: Oral, Rabbit - 14200 mg/Kg

LD₅₀: Oral, Rat - 5628 mg/Kg

LD₅₀: Skin, Rabbit - 15800 mg/Kg

LC₅₀: Inhalation, Rat - 64000 ppm

Toluene (108-88-3)

48 Hr EC₅₀ Daphnia magna: 5.46 - 9.83 mg/L [Static];

48 Hr EC₅₀ Daphnia magna: 11.5 mg/L

Inhalation LC₅₀ Rat 12.5 mg/L 4 h;

Inhalation LC₅₀ Rat >26700 ppm 1 h;

Oral LD₅₀ Rat 636 mg/kg;

Dermal LD₅₀ Rabbit 8390 mg/kg;

Dermal LD₅₀ Rat 12124 mg/kg

Acetone (67-64-1)

Oral LD₅₀ Rat: 5800 mg/kg

LC₅₀ Inhalation - rat - 8 h - 50,100 mg/m³

LD₅₀ Dermal - guinea pig - 7,426 mg/kg

Skin - rabbit - Mild skin irritation - 24 h

Eyes - rabbit - Eye irritation - 24 h

CHRONIC EFFECTS:

Component

Methanol (67-56-1)

Carcinogenic Effects: Not available
Mutagenic Effects: Not Available
Teratogenic Effects: Not Available
Developmental Toxicity: Not available
Target Organs: Eyes, CNS, skin, GI tract, and respiratory system

Toluene (108-88-3)

Carcinogenic Effects: A4 - Not classifiable for human or animal by ACGIH.
Mutagenic Effects: Not Available.
Teratogenic Effects: Not Available
Developmental Toxicity: Reproductive effects in experimental animals and in long term chemical abuse situations.
Target Organs: Long-term overexposure to toluene has been associated with impaired color vision. Also, long-term overexposure to toluene in occupational environments has been associated with hearing damage. Skin, respiratory system, Central nervous system, Heart, blood, kidneys, lungs, liver, mucous membrane, brain, eyes, lens, or cornea.

Acetone (67-64-1)

Carcinogenicity: ACGIH A4 – Not Classifiable as a Human Carcinogen
Neurotoxicity: This product contains Acetone, a central nervous system target.
Mutagenicity: No information available for product.
Reproductive: No information available for product.
Developmental: No information available for product.
Target Organs: Acetone can target the respiratory system, eyes, CNS, kidneys, hematology.

Light Hydrotreated Distillate (CAS #68410-97-9)

Carcinogenic Effects: Not Available
Mutagenic Effects: Not Available
Teratogenic Effects: Not Available
Developmental Toxicity: Not Available
Target Organs: **Routes of exposure** Inhalation. Ingestion. **Eyes** Avoid contact with eyes. Causes eye irritation. **Skin** Avoid contact with the skin. Contact with skin may cause irritation. **Inhalation** Prolonged inhalation may be harmful.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Methanol (67-56-1)

EC50 (48 h) : 13,200 mg/l Species : Rainbow trout (*Oncorhynchus mykiss*).
EC50 (48 h) : 16,000 mg/l Species : Bluegill sunfish (*Lepomis macrochirus*).
EC50 (48 h) : > 10,000 mg/l Species : Daphnia

Ecotoxicity: Toluene (108-88-3)

96 Hr EC50 *Pseudokirchneriella subcapitata*: >433 mg/L;
72 Hr EC50 *Pseudokirchneriella subcapitata*: 12.5 mg/L [static] mg/L [flow-through] (1 day old);
96 Hr LC50 *Pimephales promelas*: 12.6 mg/L [static];
96 Hr LC50 *Oncorhynchus mykiss*: 5.89-7.81 mg/L [flowthrough];
96 Hr LC50 *Oncorhynchus mykiss*: 14.1- 17.16 mg/L [static];
96 Hr LC50 *Oncorhynchus mykiss*: 5.8 mg/L [semi-static];
96 Hr LC50 *Lepomis macrochirus*: 11.0-15.0 mg/L [static];
96 Hr LC50 *Oryzias latipes*: 54 mg/L [static];
96 Hr LC50 *Poecilia reticulata*: 28.2 mg/L [semi-static];
96 Hr LC50 *Poecilia reticulata*: 50.87-70.34 mg/L [static]
48 Hr EC50 *Daphnia magna*: 5.46 - 9.83 mg/L [Static];
48 Hr EC50 *Daphnia magna*: 11.5 mg/L

Ecotoxicity: Acetone (67-64-1)

96 hour LC50 Oncorhynchus mykiss: 5540 mg/L (static)
96 hour LC50 Pimephales promelas 6210 mg/L [flow through]
96 hour LC50 Lepomis macrochirus: 8300 mg/L [static]
15 min EC50 Photobacterium phosphoreum: 14,500 mg/L
48 Hr EC50 water flea: 0.0039 mg/L
48 hour EC50 water flea: 12,700 mg/L [static]
48 hour EC50 Daphnia magna: 12,600 mg/L

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations.

Section 14: TRANSPORT INFORMATION

Proper Shipping Name: Paint related material

Hazard Class: 3

Identification No.: UN1263

Packing Group: II

Label: Flammable

Section 15: REGULATORY INFORMATION

TSCA Inventory This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

SARA 302/304 The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

SARA 313: Methanol (CAS #67-56-1) 1.0% de minimus, Toluene (CAS #108-88-3)

CERCLA The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: Toluene [CAS No.: 108-88-3] RQ = 1000 lbs. (453.6 kg), Methanol [CAS No. 67-56-1] RQ = 5,000, Acetone [CAS No. 67-64-1] RQ = 5,000.

SARA 311/312 Hazard The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard, Fire Hazard

Additional Regulatory

Remarks

Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.83(a)(13): This product contains Toluene which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: **DANGER: Contains Toluene! Harmful or fatal if swallowed! Call Physician Immediately. Vapor Harmful! KEEP OUT OF REACH OF CHILDREN!**

Section 16: OTHER SUPPLEMENTAL INFORMATION**Disclaimer:**

The information and recommendations contained in the Safety Data Sheet (SDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Our Company, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will our company be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY Our Company HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.