

PRODUCT FEATURES & APPLICATION



Touch Dry 20 min

Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

BRUSHABLE SEAM & JOINT SEALER

Stock PBGQ

Part # 500001 (918gm cans)

Colour Grey

Description:

A 100% rubberized seam & joint sealer for bare and primed metals. Excellent adhesion and is ideal for all "lap" and "flange" seams and joints. Permanently flexible. Will not crack and also holds a perfect "brush" mark to match that O.E.M. seam. Will adhere wet or dry and will not "sink" or "sag". Paintable in 20 minutes. Available in a light grey colour only.

Features:

- Grey in colour and holds a perfect brushmark
- Seals overlap joints and seams
- Adheres to painted and bare metals
- Paintable in 20 minutes
- Heavy bodied sealer remains flexible
- Adheres wet or dry
- Will not "sag" or "sink"
- Minimal shrinkage

Application Instructions:

1. Remove lid from can
2. Briefly stir material with a stir-stick or brush
3. Using a stir-stick or brush apply enough material to completely cover desired area.
4. Re-brush entire seam for uniformity.
5. Allow at least 20 minutes (20 C @ 65% R.H.) to dry before painting.

Touch Dry and Paintable 20 – 30 min

Full Cure 4 – 8 Hours

Surface Preparation:

- Surfaces must be free and clear of all contaminants.
- Use silicone & grease remover to remove any residue.
- Be sure that painted surfaces are lightly scuffed to ensure proper adhesion
- Using an air gun, blow away any dust from seams / joints before applying material.

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1-800-265-0790, ext. MSDS.

PBGQ 2 2002