

PRODUCT: MAXIM™ Multi-Fix Plastic Repair

PART NUMBER: 100898 250mL Cartridge 6 units/case

DESCRIPTION: Maxim Multi-Fix plastic repair is a two component epoxy repair material that provides speed, incredible strength and sandability. This fast setting epoxy simplifies the plastic repair process by eliminating substrate identification and adhesion promoter. Multi-Fix is ideal for fixing tears, nicks and gouges in plastic parts and other quick fix applications. Can also be applied over Maxim™ Medium Urethane Adhesive 100885, Maxim™ Fast Urethane Adhesive 100887, and Maxim™ Super Fast Urethane Adhesive 100886 as a finishing material.

PREPARATION: Wash repair areas with soap and warm water. Allow to thoroughly dry. Compressed air or heat may be applied to accelerate dry time. Apply Maxim™ Panel Prep 100881 to a clean, lint-free cloth and wipe the repair area. Sand the repair with 80 grit sandpaper. Remove sanding dust with clean compressed air. Apply Maxim™ Adhesion Promoter 100883 to the repair area and allow to dry.

APPLICATION: Apply Maxim™ Multi-Fix Plastic Repair to the repair area. Allow approximately 30 minutes. Sand to contour with 80 grit sandpaper; finish with 180 grit sandpaper. Apply primer surfacer according to paint manufacturer's recommendations.

TECHNICAL SPECIFICATIONS:

| | |
|----------------|---|
| ▪ Appearance | Dark Gray Paste |
| ▪ VOC | Refer to Section 9 of the Safety Data Sheet |
| ▪ Working Time | 4-6 minutes @ 72°F/22°C) |
| ▪ Sanding Time | 20-30 minutes |
| ▪ Paint Time | After sanding |
| ▪ Full Cure | 4 hours |

NOTE: Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

For professional use only, read all directions and warnings prior to using Evercoat® products. Keep cartridge closed and store in a cool dry place.

Safety Data Sheets can be found online at evercoat.com.