



## PRODUCT DATA

# 4155, 4157, 4167 Ultra Flex™ Seam Sealer

### DESCRIPTION:

Ultra Flex™ Seam Sealer is a rapid curing, flexible seam sealer designed for all types of painted surfaces, bare metal and primed surfaces.

### USE:

Designed to meet the flexibility requirements associated with modern unibody construction. Can be used to seal any body seam against moisture or dust and to finish skin panels. Especially useful for applications requiring extreme flexibility.

### APPLICATION:

1. Cut nozzle to desired bead size.
2. Clean all surfaces to be sealed of grease, oil and foreign matter.
3. Apply Ultra Flex™ Seam Sealer. Material may be tooled with a putty stick dampened with Acry Solvent #9783/9784.
4. Remove excess material with Acry Solvent #9783/9784.
5. Material can be painted over in 30 minutes under normal conditions.

### SALES POINTS:

- Applies easily.
- Skins fully in 3 minutes.
- Excellent tooling and adhesion.
- Paintable in 30 minutes.
- Remains flexible when dry.

### COMPETITION:

3M, Joint and Seam Sealer #08301, Flexiclear  
Kent, Hi-Tech10075/10095  
Dominion Sure Seal, 9005

(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

### PACKAGE SIZE:

- 4155 Ultra Flex™ Seam Sealer, 5 oz. (295 ml) squeeze tube, 12/case  
4157 Ultra Flex™ Seam Sealer - Beige, 11 oz. (325 ml) cartridge, 12/case  
4167 Ultra Flex™ Seam Sealer - Black, 11 oz. (325 ml) cartridge, 12/case

*DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*

