

---

**P R O D U C T   D A T A**

---

**4343**

***Zinc Rich Weld Through Primer***

**DESCRIPTION:**

Zinc Rich Weld Through Primer offers high resistance to salt and water. Requires no priming, is quick drying and is water after 15 minutes. Heat resistant up to 500°F. Zinc Rich is specifically designed for spot welding. Long protection for all metallic surfaces.

**APPLICATION:**

Surface should be clean, dry and free of rust. Shake can well before using. Hold can 10 to 12 inches from surface and spray with consistent, even strokes for uniform coverage. Invert can and spray until valve is free of material to prevent clogging.

**SALES POINTS:**

- Excellent corrosion protection (98% zinc).
- Superior adhesion.
- Fast drying.
- Resists sags and settling.

**COMPETITION:**

3M Weld-Thru Coating

---

*(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).*

**PACKAGE SIZE:**

#4343 Zinc Rich weld Through Primer, 16 oz. aerosol, 6/case

*DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*

