
P R O D U C T D A T A

4423

Amber Rustproofing

DESCRIPTION:

Body-Tec[®] Amber Rustproofing matches OEM appearance while providing superior rust protection. Abrasion resistant coating will flow into hard to reach seams. Designed for replacement panels or new car rustproofing and restores the repair of existing corrosion protection to original specifications found on the interior of fender and panel replacements. Note: Amber Rustproofing is not recommended for use on exposed areas such as luggage compartments or engine bays, as the material remains tacky after application.

TECHNICAL DATA:

APPEARANCE:	Amber Liquid
NET WEIGHT:	1 lb, 1 oz. (483 gr)
SOLVENTS:	Hexane, Acetone, Butanes and Hydrocarbons
V.O.C. CONTENT:	2.42 #/gal (290g/l) and 28% by weight

APPLICATION:

1. Shake well.
2. Clean surface using SCAT #6311 or General Purpose Solvent #4074.
3. Holding can 10 - 12 inches from the surface, apply 2 - 3 light even coats. Short, even strokes produce best results.
4. Remove overspray with General Purpose Solvent #4074.

Note: Allow several hours for flammable vapors to escape when product is sprayed in enclosed areas. Flush with compressed air to help remove vapors.

SALES POINTS:

- Remains tacky and flexible once applied.
- Will flow into hard to reach areas.
- Abrasion resistant.
- Excellent high and low temperature performance.

(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

PACKAGE SIZES:

#4423 Amber Rustproofing, 24 oz. Aerosol, 6/case

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.

