
P R O D U C T D A T A

6417
Kicker Urethane Accelerator

DESCRIPTION:

Transtar Kicker Accelerator is designed to accelerate the curing, dust, tack and tape times of Transtar Acrylic Urethane Primers and Clear Coats with no sacrifice of pot life. When Kicker is used according to the directions, it can save time and cost, by improving shop productivity.

TECHNICAL DATA:

APPEARANCE:	Clear Liquid
% SOLIDS:	1.60% (by weight)
V.O.C. CONTENT:	8.00 #/gal (960 g/l)
SHELF LIFE:	One year (unopened)

MIX RATIOS:

The mixing ratios listed below are guidelines only and may react differently under varied shop conditions like temperature, humidity, and air movement. Proper film builds, dry times, reducer choices, temperatures and activators remain key factors for optimum product performance.

Primers/Primer Surfacers

6921, 6401

Clear Coats

6531, 6571, 6771, 6781, 6791, 6841, 6861

Kicker #6417 Ready-to-Spray Quart

1/2 oz. up to 1 oz.

Kicker #6417 Ready-to-Spray Quart

1/2 oz.

CAUTIONS:

DO NOT use in any products other than those listed. Excessive amounts of Kicker may cause yellowing, staining or embrittlement.

COMPETITION:

PPG DX 84, DXR 81

DuPont 289S

The information contained on this data sheet is believed to be accurate at the time of printing. However, regulations governing V.O.C. levels are subject to change from time to time. Please consult with your local regulatory office for the latest regulations.

(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin.)

PACKAGE SIZES:

#6417 8 oz. Twin Neck Plastic Measuring Bottle, 6/case

