

# U-POL

## PRODUCTS

# FIBRAL

### Sandable Fiber Glass Putty

#### Description

U-POL FIBRAL is a short strand fiber glass putty used for bridging holes in steel and fiber glass panels. U-POL FIBRAL putty forms a hard durable surface, however its short strand formulation enable it to be easily applied and sanded. U-POL FIBRAL has been specially formulated for the professional it can be top coated with putty or directly top coated with paint.

#### Surface preparation and instructions for use

U-POL FIBRAL putty can be used on the following ;-

- Steel - degrease and abrade with 80 grit paper.
- Fully cured paint surfaces - degrease and sand with 180 grit paper.
- Fiber Glass - degrease and sand with 80 grit paper.

#### Mixing ratio

100% by weight U-POL FIBRAL 5% by weight U-POL hardener for putty. The exact mixing ratio is not critical although over or under catalyzation may affect the gel time.

#### Tools

Mixing board, filler knife, plastic or rubber spreader.

#### Pot life

U-POL FIBRAL is rapid curing and non shrinking once mixed, 4-5 mins. at 70°F with 5% hardener.

#### Drying time

Sandable after 20 mins. at 70°F.

#### Application

U-POL FIBRAL is a smooth creamy putty it will not sag even on vertical surfaces.

#### Sanding

Begin sanding with 80 grit paper using finer grades to finish such as 120 then 220 grit, for rotary sanding equipment a hard back plate is recommended. Hand sanding can be done wet or dry.

#### Top-Coating

U-POL FIBRAL can be top-coated with most paint systems.

#### Product codes

**UP715** - 750ml / 950g Can.

**UP716** - 900ml Can.

**UP717** - 1.3L / 1600g Dispenser Cartridge.

U-POL c/o Sanders & Associates Inc., 1263 Route 31 South, Lebanon, NJ 08833

Tel: (908) 730 8858 or (800) 340 7824 Fax: (908) 730 6621 or (800) 787 5150

E-mail: [upol@earthlink.net](mailto:upol@earthlink.net) Website: [www.u-pol.com](http://www.u-pol.com)