

Finish Pro 5405 Slow Lacquer Thinner

**I. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****MANUFACTURER'S NAME:**

CUMBERLAND PRODUCTS INCORPORATED

**ADDRESS:**50 COMMERCE PARKWAY  
HODGENVILLE, KY 42748

EMERGENCY PHONE : (800) 424 - 9300

INFORMATION PHONE : (800) 223 - 1918

FAX NUMBER : (800) 500 - 9812

PRODUCT NAME	Finish Pro 5405 Slow Lacquer Thinner
PRODUCT CODE	707670
PRODUCT USE DESCRIPTION	No data

**2. HAZARDS IDENTIFICATION****Emergency Overview****Appearance:** liquid, Water-white

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS.

**Potential Health Effects****Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye contact**

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

**Skin contact**

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage.

Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

**Ingestion**

Swallowing this material may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (*see* Section 8.).

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions), Upper respiratory tract, Kidney, Liver, pancreas, Central nervous system, Heart, blood-forming system, auditory system, Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), runny nose, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, temporary changes in mood and behavior, muscle cramps, Weakness, pain in the abdomen and lower back, Blurred vision, Shortness of breath, Lack of coordination, confusion, irregular heartbeat, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), high blood sugar, visual impairment (including blindness), coma

Finish Pro 5405 Slow Lacquer Thinner

**Target Organs**

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Exposure to lethal concentrations of methanol has been shown to cause damage to organs including liver, kidneys, pancreas, heart, lungs and brain. Although this rarely occurs, survivors of severe intoxication may suffer from permanent neurological damage. Prolonged intentional toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Prolonged intentional toluene abuse may lead to hearing loss progressing to deafness. In addition, while noise is known to cause hearing loss in humans, it has been suggested that workers exposed to organic solvents, including toluene, along with noise may suffer greater hearing loss than would be expected from exposure to noise alone. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible kidney effects, blood abnormalities, liver abnormalities, respiratory tract damage (nose, throat, and airways), effects on hearing, central nervous system damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: kidney damage, visual impairment

**Carcinogenicity**

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

**Reproductive hazard**

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans. Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain.

<b>3. COMPOSITION/INFORMATION ON INGREDIENTS</b>
--

Hazardous Components	CAS-No.	Concentration
TOLUENE	108-88-3	>=40-<50%
METHANOL	67-56-1	>=15-<20%
ACETONE	67-64-1	>=15-<20%
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	>=15-<20%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	>=1.5-<5%

<b>4. FIRST AID MEASURES</b>
------------------------------

**Eyes**

If symptoms develop, immediately move individual away from exposure and into fresh air.

Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin**

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

**Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation**

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Finish Pro 5405 Slow Lacquer Thinner

**Notes to physician**

**Hazards:** Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

**Treatment:** No information available.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Water spray, Dry chemical, Carbon dioxide (CO<sub>2</sub>)

**Hazardous combustion products**

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, Ketones, Organic acids, organic compounds

**Precautions for fire-fighting**

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

**Environmental precautions**

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

**Methods for cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**Other information**

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapors/mists with a water spray jet.

**7. HANDLING AND STORAGE****Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document N1-PA 77.

**Storage**

Store in a cool, dry, ventilated area, away from incompatible substances.

<b>8. EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
---

**Exposure Guidelines****TOLUENE****108-88-3**

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL) :	100 ppm
NIOSH	Recommended exposure limit (REL):	375 mg/m <sup>3</sup>
NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	560 mg/m <sup>3</sup>
OSHA Z2	Short term exposure limit	200 ppm
OSHA Z2	Permissible exposure limit	300 ppm
OSHA Z2	Permissible exposure limit	500 mg/m <sup>3</sup>

**ACETONE****67-64-1**

ACGIH	time weighted average	500 ppm
ACGIH	Short term exposure limit	750 ppm
NIOSH	Recommended exposure limit (REL):	250 mg/m <sup>3</sup>
NIOSH	Recommended exposure limit (REL):	590 ppm
OSHA Z1	Permissible exposure limit	1,000 mg/m <sup>3</sup>
OSHA Z1	Permissible exposure limit	2,400 ppm

**METHANOL****67-56-1**

ACGIH	time weighted average	200 ppm
ACGIH	Short term exposure limit	250 ppm
NIOSH	Recommended exposure limit (REL):	200 ppm
NIOSH	Recommended exposure limit (REL):	260 mg/m <sup>3</sup>
NIOSH	Short term exposure limit	250 ppm
NIOSH	Short term exposure limit	325 mg/m <sup>3</sup>
OSHA Z1	Permissible exposure limit	200 ppm
OSHA Z1	Permissible exposure limit	260 mg/m <sup>3</sup>

**SOLVENT NAPHTHA (PETROLEUM),****LIGHT ALIPHATIC****100-41-4**

OSHA Z1	time weighted average	500 ppm
ACGIH	time weighted average	300 ppm
ACGIH	time weighted average	1,370 ppm

**ETHYLENE GLYCOL MONOBUTYL ETHER****111-76-2**

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	5 ppm
NIOSH	Recommended exposure limit (REL):	24 mg/m <sup>3</sup>
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	240 mg/m <sup>3</sup>

**General advice**

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Exposure controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Finish Pro 5405 Slow Lacquer Thinner

**Eye protection**

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection**

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use. Wear resistant gloves (consult your safety equipment supplier). Discard gloves that show tears, pinholes, or signs of wear.

**Respiratory protection**

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

<b>9. PHYSICAL AND CHEMICAL PROPERTIES</b>
--

<b>Physical state</b>	liquid
<b>Form</b>	No data
<b>Color</b>	Water-Clear
<b>Odor</b>	No data
<b>Boiling point/boiling range</b>	No data
<b>pH</b>	No data
<b>Flash point</b>	(>=) -20.00 °C Tag closed cup
<b>Evaporation rate</b>	No data
<b>Lower explosion limit/Upper explosion limit</b>	No data
<b>Vapor pressure</b>	No data
<b>Vapor density</b>	No data
<b>Density</b>	0.815 g/cm <sup>3</sup> @ 68 °F / 20 °C 6.790 lb/gal @ 68 °F / 20 °C
<b>Solubility</b>	No data
<b>Partition coefficient: n-octanol/water</b>	No data
<b>log Pow</b>	No data available
<b>Autoignition temperature</b>	No data

<b>10. STABILITY AND REACTIVITY</b>
-------------------------------------

**Stability**

Stable.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible products**

Acids, alkalis, aluminum, Amines, Ammonia, calcium hypochlorite, halogens, hypochlorites, Lead, peroxides, Reducing agents, sodium, Strong oxidizing agents, Zinc

**Hazardous decomposition products**

Aldehydes, carbon dioxide and carbon monoxide, formaldehyde, Hydrocarbons, organic compounds

**Hazardous reactions**

Product will not undergo hazardous polymerization.

**Thermal decomposition**

No data

Finish Pro 5405 Slow Lacquer Thinner

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Acute oral toxicity**

TOLUENE:	LD 50 Rat: 2,600 - 7,500 nig/kg
METHANOL:	LD L0 Human: 300 mg/kg
ACETONE:	LD 50 Rat: 5,800 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:	LD 50 Rat: > 8,000 mg/kg
ETHYLENE GLYCOL MONOBUTYL ETHER:	LD 50 Guinea pig: 1,200 mg/kg

**Acute inhalation toxicity**

TOLUENE:	LC 50 Rat: 8000 ppm, 4 h
METHANOL:	LC 50 Rat: 64,000 ppm, 4 h
ACETONE:	LC 50 Rat: > 16,000 ppm, 4 h
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:	LC 50 Rat: 3,400 ppm, 4 h
ETHYLENE GLYCOL MONOBUTYL ETHER:	LD 50 Guinea pig: >633 ppm, 1h

**Acute dermal toxicity**

TOLUENE:	LD 50 Rabbit: 12,124 mg/kg
METHANOL:	LD 50 Rabbit: 12,800 mg/kg
ACETONE:	LD 50 Rabbit: > 20,000 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:	LD 50 Rat: > 4,000 mg/kg
ETHYLENE GLYCOL MONOBUTYL ETHER:	LD 50 Guinea pig: >2,000 mg/kg

<b>12. ECOLOGICAL INFORMATION</b>
-----------------------------------

**Biodegradability**

TOLUENE:	no data available
METHANOL:	no data available
ACETONE:	no data available
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:	no data available
ETHYLENE GLYCOL MONOBUTYL ETHER:	no data available

**Bioaccumulation**

TOLUENE:	Species: Ide, silver or golden orfe (Leuciscus idus) Exposure time: 3 d Dose: 0.05 mg/l Bioconcentration factor (BCF): 94 Method: Not reported
----------	--

METHANOL:	Species: Green algae (Chlorella fusca vacuolata) Exposure time: 24 h Dose: 0.05 mg/l Bioconcentration factor (BCF): 28,400 Method: Static
-----------	---

ACETONE:	no data available
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:	no data available
ETHYLENE GLYCOL MONOBUTYL ETHER:	no data available

**Ecotoxicity effects****Toxicity to fish**

TOLUENE:	96 h LC 50 Rainbow trout, donaldson trout (Oncorhynchus mykiss): 5.80 mg/l Method: Renewal Mortality 96 h LC 50 Fathead minnow (Pimephales promelas): 12.60 mg/l Method: Static Mortality
METHANOL:	no data available

**SAFETY DATA SHEET**

Revision Date: 01/14/2010

Print Date: 11/30/2012

MSDS Number: 000000148127

Version: 1.2

Finish Pro 5405 Slow Lacquer Thinner

ACETONE

96 h LC 50 Rainbow trout,donaldson trout  
(Oncorhynchus mykiss): 4,740.00 - 6,330.00 mg/I

Method: Static

Mortality96 h LC 50 Bluegill (Lepomis  
macrochirus): 8,300.00 mg/1

Method: Static

Mortality 96 h LC 50 Fathead minnow (Pimephales  
promelas): 8,733.00 - 9,482.00 mg/I

Method: Flow through

Mortality

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**Toxicity to daphnia and other aquatic invertebrates.**

TOLUENE:

48 h EC 50 Waterflea (Daphnia magna): 6.00 mg/I

Method: Static

Intoxication

METHANOL:

48 h EC 50 Water flea (Daphnia magna): > 10,000.00 mg,/1

Method: Static

Intoxication

ACETONE:

no data available

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**Toxicity to algae**

TOLUENE:

no data available

METHANOL:

no data available

ACETONE:

no data available

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**Toxicity to bacteria**

TOLUENE:

no data available

METHANOL:

no data available

ACETONE:

no data available

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**Biochemical Oxygen Demand (BOD)**

TOLUENE:

no data available

METHANOL:

no data available

ACETONE:

no data available

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**Chemical Oxygen Demand (COD)**

TOLUENE:

no data available

METHANOL:

no data available

ACETONE:

no data available

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**Additional ecological information**

TOLUENE:

no data available

METHANOL:

no data available

ACETONE:

no data available

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

no data available

ETHYLENE GLYCOL MONOBUTYL ETHER:

no data available

**SAFETY DATA SHEET**

Finish Pro 5405 Slow Lacquer Thinner

Revision Date: 01/14/2010  
 Print Date: 11/30/2012  
 MSDS Number: 000000148127  
 Version: 1.2

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations.

**14. TRANSPORT INFORMATION**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

UN 1993	Flammable liquids, n.o.s. (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)	3		II	
---------	---	---	--	----	--

**U.S. DOT - RAIL**

UN 1993	Flammable liquids, n.o.s. (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)	3		II	
---------	---	---	--	----	--

**U.S. DOT - INLAND WATERWAYS**

UN 1993	Flammable liquids, n.o.s. (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)			II	
---------	---	--	--	----	--

**TRANSPORT CANADA - ROAD**

UN 1993	FLAMMABLE LIQUID, N.O.S. 3 (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)			II	
---------	--	--	--	----	--

**TRANSPORT CANADA - RAIL**

UN 1993	FLAMMABLE LIQUID, N.O.S. 3 (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)			II	
---------	--	--	--	----	--

**TRANSPORT CANADA - INLAND WATERWAYS**

UN 1993	FLAMMABLE LIQUID, N.O.S. 3 (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)			II	
---------	--	--	--	----	--

**INTERNATIONAL MARITIME DANGEROUS GOODS**

UN 1993	FLAMMABLE LIQUID, N.O.S. 3 (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)			II	
---------	--	--	--	----	--

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

UN 1993	Flammable liquid, n.o.s. (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)			II	
---------	--	--	--	----	--

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

UN 1993	Flammable liquid, n.o.s. (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)	3		II	
---------	--	---	--	----	--

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

UN 1993	LIQUIDO INFLAMABLE, N.E.P. (ACETONE, ALIPHATIC PETROLEUM NAPHTHA)	3		11	
---------	--	---	--	----	--

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID



Finish Pro 5405 Slow Lacquer Thinner

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**15. REGULATORY INFORMATION**

California Prop. 65  
 WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.  
 TOLUENE  
 BENZENE

**SARA Hazard Classification**

Fire Hazard  
 Acute Health Hazard

**SARA 313 Component(s)**

TOLUENE 48.02 %  
 METHANOL 17.00 %  
 ETHYLENE GLYCOL MONOBUTYL ETHER 1.98%

**New Jersey RTK Label Information**

TOLUENE 108-88-3  
 METHANOL 67-56-1  
 ACETONE 67-64-1  
 SOLVENT NAPHTHA (PETROLEUM). LIGHT ALIPHATIC 64742-89-8  
 ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2

**Pennsylvania RTK Label Information**

TOLUENE 108-88-3  
 METHANOL 67-56-1  
 ACETONE 67-64-1  
 SOLVENT NAPHTHA (PETROLEUM), LIGHT ALCPHATIC 64742-89-8  
 ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2  
 BENZENE 71-43-2

**Notification status**

EU. EINECS y (positive listing)  
 US. Toxic Substances Control Act y (positive listing)  
 Australia. Industrial Chemical (Notification and Assessment) Act y (positive listing)  
 Canada. Canadian Environmental Protection Act (CEPA). y (positive listing)  
 Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)  
 Japan. Kashin-Hou Law List y (positive listing)  
 Korea. Toxic Chemical Control Law (TCCL) List y (positive listing)  
 Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act y (positive listing)  
 China. Inventory of Existing Chemical Substances y (positive listing)  
 New Zealand. Inventory of Chemicals (NZIoC), as published  
 by ERMA New Zealand y (positive listing)

**Reportable quantity - Product**

US. EPA CERCLA Hazardous Substances (40 CFR 302) 2082 lbs

**Reportable quantity-Components**

TOLUENE 108-88-3 1000 lbs

	<b>HMIS</b>	<b>NFPA</b>
Health	2	2
Flammability	3	3
Physical hazards	--	
Instability		0
Specific Hazard	--	

Finish Pro 5405 Slow Lacquer Thinner

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Finish Pro 5405 Slow Lacquer Thinner

**VOC and HAP REPORT**

<b>VOC Content (as formulated)</b>	82.03 %
<b>Total VOC Content</b>	6.83 lbs/gal / 818.414 g/l
<b>VOC Content (SCAQMD)</b>	5.66 lbs/gal / 678.217 g/l
<b>VOC Vapor Pressure @ 20°C (SCAQMD)</b>	73.27 hPa
<b>Calculated HAP Total</b>	65.02%
TOLUENE 108-88-3	48.02%
METHANOL 67-56-1	17.00%
<b>Calculated Organic HAP Total</b>	65.02%
TOLUENE 108-88-3	48.02%
METHANOL 67-56-1	17.00%

Hazardous Air Pollutants reported on this document are limited to those that are defined as hazardous under 29 CFR 1910.1200. It is possible that there are other Hazardous Air Pollutants in this product at levels that are not reportable by the OSHA Hazard Communication Standard. Certain air regulations require that these components be included in determinations of total HAP emissions. If you require information on the unreported Hazardous Air Pollutants, please contact your Cumberland Products Inc. account representative.

This information has been gratuitously provided by Cumberland Products Inc.. Although it is intended to be accurate, Cumberland Products Inc. DISCLAIMS ANY AND ALL LIABILITY, EITHER EXPRESS OR IMPLIED. This information is based on many factors beyond Cumberland's control, including but not limited to the completeness and accuracy of information received, or the conditions prevailing when operations were observed and/or sampled. In choosing to rely on or use this information, you assume all risk including the results obtained and agree to indemnify, defend and hold harmless Cumberland Products Inc. against any and all claims. All recommendations or suggestions must be evaluated by you to determine their applicability or suitability for your particular program. Cumberland Products Inc. is not engaged in rendering legal or other professional service, and if such service is required, a competent professional should be retained. Any information claimed by Cumberland Products Inc. to be confidential or proprietary is not to be disclosed to any third party.